

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A non-transitory computer-readable storage medium for storing instructions for invoking a function of a diagnostic instrument, the code, once executed, causing the instrument to display:

a first navigational menu including at least one display element, the at least one display element having a touch sensitive active region therein and a graphical representation of functionality invoked via user selection of the display element by user contact with the touch sensitive active region, the display element and the touch sensitive active region being located on the same surface of a display screen of the diagnostic instrument;

a second navigational menu configured to be displayed responsive to contact on the touch sensitive active region of the at least one display element, the second navigational menu including a selection group related to a test suite of the diagnostic instrument; and

an instrument identity banner including details of the type and status of the diagnostic instrument.

2. (Previously Amended) The medium of claim 1, wherein the selection group includes a plurality of display elements, each of the plurality of display elements having a touch sensitive active region to enable user selection of the plurality of display elements.

3. (Previously Amended) The medium of claim 1, wherein the selection group includes fewer than ten display elements to permit discrete touch sensitive selection of each of the fewer than ten display elements.

4. (Previously Amended) The medium of claim 1, wherein the first navigational menu includes at least six display elements, each of the at least six display elements having a discrete touch sensitive active region sized to permit finger tip selection.

5. (Previously Amended) The medium of claim 1, wherein the at least one display element comprises

a textual description of functionality invoked by user selection of the display element.

6. (Previously Amended) The medium of claim 1, wherein the touch sensitive active region comprises an approximately circular shape with a diameter of at least $\frac{3}{8}$ inch.

7. (Previously Amended) The medium of claim 1, wherein the touch sensitive active region comprises an area having a polygonal shape of at least $\frac{1}{4}$ square inch.

8. (Previously Amended) The medium of claim 1, wherein the touch sensitive active region comprises an area of at least $\frac{1}{10}$ that of the screen area.

9. (Previously Amended) The medium of claim 1, wherein the first and the second navigational menus are displayed on a touch screen device sized and positioned so as to be responsive to a gloved finger.

10. (Withdrawn) A method for operating a diagnostic instrument, the method comprising the steps of:

providing a user interface on a screen including a display element having an active region, the active region corresponding in size to a human finger tip contact area for enabling human finger tip selection of the display element;

receiving coordinate information responsive to user contact with the screen, the coordinate information indicating a location on the screen;

determining whether the location corresponds to the active region; and

sending a command to the diagnostic instrument responsive to the determining step.

11. (Withdrawn) The method of claim 10, further comprising:
receiving a result from the diagnostic instrument; and
storing the result in a database.
12. (Withdrawn) The method of claim 10, wherein the active region comprises an
approximately circular shape with a diameter of at least $3/8$ inch.
13. (Withdrawn) The method of claim 10, wherein the active region comprises an area
having a polygonal shape of at least $1/4$ square inch.
14. (Withdrawn) The method of claim 10, wherein the active region comprises an area of at
least $1/10$ that of the screen area.
15. (Withdrawn) The method of claim 10, wherein the screen comprises a touch screen
device configured to be responsive to a gloved finger.
16. (Withdrawn) An apparatus for operating a diagnostic instrument, the apparatus
comprising:
a user interface module configured to provide a user interface on a screen including a display
element having an active region, the active region corresponding in size to a human finger tip contact
area for enabling human finger tip selection of the display element;
a display module configured to receive coordinate information responsive to user contact
with the screen and determining whether the coordinate information corresponds to the active region;
and
an instrument interface module configured to send a command to the diagnostic instrument
responsive to a signal from the display module.

17. (Withdrawn) The apparatus of claim 16, further comprising:

a language module configured to provide a textual description for the display element.

18. (Withdrawn) The apparatus of claim 16, further comprising:

a database module configured to receive and to store a result from the diagnostic instrument.

19. (Withdrawn) The apparatus of claim 16, wherein the active region comprises an

approximately circular shape with a diameter of at least $\frac{3}{8}$ inch.

20. (Withdrawn) The apparatus of claim 16, wherein the active region comprises an area

having a polygonal shape of at least $\frac{1}{4}$ square inch.

21. (Withdrawn) The apparatus of claim 16, wherein the active region comprises an area of

at least $\frac{1}{10}$ that of the screen area.

22. (Withdrawn) The apparatus of claim 16, wherein the screen comprises a touch screen

device configured to be responsive to a gloved finger.

23. (Withdrawn) A computer readable medium including program code for operating a

diagnostic instrument, the medium comprising:

a first program code module configured to provide a user interface on a screen including a display element having an active region, the active region corresponding in size to a human finger tip contact area for enabling human finger tip selection of the display element;

a second program code module configured to receive coordinate information responsive to user contact with the screen and determining whether the coordinate information corresponds to the active region; and

a third program code module configured to send a command to the diagnostic instrument responsive to a signal from the display module.

24. (Withdrawn) An apparatus for operating a diagnostic instrument, the apparatus comprising:

means for providing a user interface on a screen including a display element having an active region, the active region corresponding in size to a human finger tip contact area for enabling human finger tip selection of the display element;

means for receiving coordinate information responsive to user contact with the screen and determining whether the coordinate information corresponds to the active region; and

means for sending a command to the diagnostic instrument responsive to a signal from the display module.